



CX

UNIVERSAL CALL POINT

The CX Universal Call Point combines a number of features into one package, simplifying selection and reducing stock variants. Designed to provide the facilities most frequently used, the Universal is the easy answer for the majority of conventional installations.

- PROVEN DESIGN APPROVED AND CERTIFIED TO EN54-11
- SECURE & CONVENIENT CLIP FIT COVER
- USE OF GLASS OR PLASTIC RESETTABLE ELEMENT WITHOUT MODIFICATION
- SUPERIOR LED ALARM INDICATION
- BACK BOX
- WP VERSION SUITABLE FOR OUTDOOR USE

Specification

Voltage	9 - 30Vdc
Resistors	470 / 680
Element Type	Glass / Plastic (resettable)
Temperature	- 10°C to + 55°C - 25°C to + 70°C (WP)
Protection	IP24D IP66 (WP)
Construction	ABS
Weight	0.19Kg 0.22Kg (WP)
Colours	Red*

* Other colours available - minimum order required.

KIT COMPRISES

- A CXL call point with high visibility LED alarm indicator
- Choice of connection for 470R or 680R resistors
- Fitted glass element
- Supplied resettable element with alarm flag
- Unique Test / reset / cover removal key
- Back box with fixing screws
- Installation leaflet with drilling template for back box